

MATERIAL DETAILS				
Parts	Standard	Yield Point	Technical Drawing No.	
5 Foot Ring	S235JR EN 10025	-	-	10 - 017
4 Body Lower	S1310 NB	315	-	-
3 Body Upper	S265 NB	290	-	50 - 016
2 Valve Boss	S45 EN 10025	-	-	40 - 024
1 Shroud	S235JR EN 10025	-	-	20 - 016

PRODUCTION METHODS	
Directive	2010/35/EU
Standard	EN 1591 MAR 2017 acc to ADR 2017
Heat Treatment	890 °C - 930 °C
Shot Blasting	SA 2.5
Zinc Coating	min 20 µm
Primer Coating	min 20 µm
Painting	Polyester Powder Paint min 30 µm
Total Coating	min 70 µm
Other Notes	-

CYLINDER SPECIFICATION	
Content	LPG
Content Mass	11 KG
Volume Limits	min 26.2 L
Tests Limits	-
Test Pressure	30 BAR
Burst Pressure	67.5 BAR
Pure Pressure	-
Color (main)	RAL 6029 GREEN
Color (top)	RAL 9003 WHITE
Color (other)	-
Valve Type	-

APPROVAL			
	Name	Date	Sign
Drawn by	N. ARSJO	18.09.12	
Controlled by	E. RENVOLU		
Approved by	D. TENDEMER		

IDENTIFICATION OF THE DRAWING

CZECH REPUBLIC / PRIMAŠAS

26.2 L LPG CYLINDER

CK - 26.2 - 02 - 04

80-26-02-02-04-00-70-02-01

EVAS
EVAS s.r.o. s ústředním
zářadím