

Technical documentation according to Regulation EU 2015/1185

Manufacturer	Panadero AB, S.L
Address	Avenida 5ª 13-15, 02007 Albacete, Spain
E-Mail	info@panadero.com
Website	www.panadero.com
Telephone	+34 967 59 24 00

THIS DECLARATION OF CONFORMITY IS ISSUED FOR THE FOLLOWING PRODUCT:							
Model identifiers		Montblanc Ecodesign N° 18802					
Equivalent models							
Notified body and test reports		N° 0370 17/15468-2150 17/15468-2151 ; 39-13896/1/T					
Harmonized technical specification		EN 13240:2001 & A2:2004; EN 16510-1					
Other applied standards/technical specification		CEN/TS 15883:2010					
Indirect heating functionality:		No					
Indirect heat output		0 kW					
Direct heat output		9,8 kW					
Efficiency at nominal heat output		80,7 %					
Energy Efficiency Index (EEI):		107,02					
Seasonal space heating energy efficiency		70,7%					
FUEL	PREFERRED FUEL	OTHER SUITABLE FUEL	η s (%)	EMISSIONS AT NOMINAL HEAT OUTPUT			
				PM	OGC mg/ Nm³ (13% O₂)	CO	NOx
Wood logs with moisture content ≤20%	Yes	No	80,7	30	70	1250	160
Compressed wood with moisture content ≤12%	No	Yes					
				EMISSIONS AT NOMINAL HEAT OUTPUT			
				PM	OGC mg/ Nm³ (13% O₂)	CO	NOx
				N/A	N/A	N/A	N/A
CHARACTERISTICS WHEN OPERATING WITH THE PREFERRED FUEL							
ITEM	SYMBOL	VALUE	UNIT	ITEM	SYMBOL	VALUE	UNIT
HEAT OUTPUT				USEFUL EFFICIENCY, BASED ON NET CALORIFIC VALUE (NCV)			
Nominal heat output:	P _{nom}	9,8	kW	Useful efficiency at nominal heat output	η _{th,nom}	80,7	%
Minimum heat output	P _{min}	N/A.	kW	Useful efficiency at minimum heat output	η _{th,min}	N/A	%
AUXILIARY ELECTRICITY CONSUMPTION				TYPE OF HEAT OUTPUT/ROOM TEMPERATURE CONTROL			
At nominal heat output	e _{lmax}	N/A	kW	Single stage heat output, no room temperature control			Yes
At minimum heat output	e _{lmin}	N/A	kW	Two or more manual stages, no room temperature control			No
In standby mode	e _{lSB}	N/A	kW	With mechanic thermostat room temperature control			No
				With electronic room temperature control			No
				With electronic room temperature control plus day timer			No
				With electronic room temperature control plus week timer			No
POWER REQUIREMENT OF THE PILOT FLAME				OTHER CONTROL OPTIONS			
Pilot flame power requirement	P _{pilot}	N/A	kW	Room temperature control, with presence detection			No
				Room temperature control, with open window detection			No
				With distance control option			No
Specific precautions for assembly, installation, or maintenance.	Fire protection and safety distances to combustible building materials must be observed under all circumstances. A sufficient supply of combustion air must always be guaranteed. Air suction systems can interfere with the combustion air supply.						

The undersigned is responsible for the manufacture and conformity with the declared performance.



Miguel Panadero Denia, Owner
Albacete, 01.01.2022